



PRODUCT NUMBER ORDER

93 02-010 15-05 R

1 2 3 4 5 6

- 1 PRODUCT NMAE:93-USB SERIES
- 2 PRODUCT :02-FEMALE
- 3 POSITION OF CONTACT (010=10PIN)
- 4 PLATING TYPE:
- 5 15:15U" ON CONTACT AREA,SOLDER -TAIL 1-3 G/F
- 05:STREAM NO.
- 6 R-REEL PACKAGE

DETAIL:A

PCB LAYOUT(TOP VIEW)

(TOLERANCE:±0.05)

NOTE:

- 1. ELECTRICAL CHARACTERISTICS
- 1-1. CONTACT RESISTANCE: 80 MILLIOHMS MAX.
- 1-2. INSULATION RESISTANCE: 1,000 MEGOHMS MIN.
- 1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC MIN FOR 1 MINUTE.
- 2-2. DURABILITY: 10,000 CYCLES
- 2-3. PRODUCT COMPLIED WITH HSF

4	CONTACT 02	5	PHOSPHOR BRONZE	GOLD PLATED OVER ALL
3	CONTACT 01	5	PHOSPHOR BRONZE	GOLD PLATED OVER ALL
2	HOUSING	1	L.C.P	COLOR:BLACK
1	SHELL	1	PHOSPHOR BRONZE	TIN 100U" PLATING
NO.	DESCRIPTION	QTY	MATERIAL	NOTE

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS:	ANGLES:
X :±0.5	X :±2°
X.X :±0.20	X.X.X :±1°
X.XX :±0.10	

TITLE	MINI USB 10PIN 1.0H WHITH POST CONN ASSEM.
DWN	ALLEN
CHKD	KEVIN
APVD	ERIC.W
PART NO:	9302-01015-04R
SCALE:1:1	UNIT: MM
SIZE: A3	SHEET: 1 OF 1
REV: A	

深圳市精密兴业有限公司
SHENZHEN KRCONN TECHNOLOGY CO., LTD

CUSTOMER COPY

REV.	ECN NO OR DESCRIPTION	REVISED	DATE
A	PROPOSE ONLY	ALLEN	04/14/08